



## Johnson Controls Metasys Slave Interface Module

### MVI56-N2

*Ideal for Energy Management Applications.*

*Applications benefiting from the N2 module are prevalent in commercial building and energy management projects. Single or multiple processor applications will benefit through reduced installation costs and increased functionality.*

### How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

#### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

#### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

#### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

#### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

#### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

## Johnson Controls Metasys Slave Interface Module

### MVI56-N2

The MVI56 Johnson Controls Metasys Slave Communication Module allows Rockwell Automation ControlLogix I/O compatible processors to interface easily with other Johnson Controls N2 master devices.

### Features and Benefits

The MVI56-N2 module acts as an input/output module between the Johnson Controls Metasys network and the Rockwell Automation ControlLogix backplane. The module acts as a slave receiving commands from a master device. The data transfer from the ControlLogix processor is asynchronous from the actions on the Johnson Controls Metasys network. An internal database in the module exchanges data between the processor and the Johnson Controls Metasys Master (NCM, N-30, NAE, NIE).

### General Specifications

- Single Slot – 1756 backplane compatible
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module
- Ladder Logic is used for data transfer between module and processor. Sample ladder file included.
- Configuration data obtained from configuration text file downloaded to module. Sample configuration file included
- Local or remote rack

### Hardware Specifications

| Specification          | Description   |
|------------------------|---|
| Backplane Current Load | 800 mA @ 5 V  |
| Operating Temperature  | 0 to 60°C (32 to 140°F)   |
| Storage Temperature    | -40 to 85°C (-40 to 185°F)  |
| Shock:                 | 30g Operational<br>50g non-operational  |
| Vibration:             | 5 g from 10 to 150 Hz   |
| Relative Humidity      | 5 to 95% (non-condensing)   |
| LED Indicators:        | Module Status<br>Backplane Transfer Status<br>Application Status<br>Serial Activity |

| Specification  | Description   |
|--|---|
| <b>Debug/Configuration port (CFG)</b>  |   |
| CFG Port (CFG)   | RJ45 (DB-9M with supplied cable)<br>RS-232 only   |
| <b>Application ports (PRT1 &amp; PRT2)</b>                                       |   |
| Full hardware handshaking control, providing radio, modem and Multi-drop support |   |
| Software configurable communication parameters                                   | Baud rate: 110 to 115,200 baud, depending on protocol<br>RS-232, 485 and 422<br>Parity: none, odd or even<br>Data bits: 5, 6, 7, or 8<br>Stop bits: 1 or 2<br>RTS on/off delay: 0 to 65535 ms |
| App Ports (P1,P2) (Serial modules)   | RJ45 (DB-9M with supplied cable)<br>RS-232 handshaking configurable<br>500V Optical isolation from backplane  |
| Shipped with Unit  | RJ45 to DB-9M cables for each port<br>6-foot RS-232 configuration cable   |

## Functional Specifications

Some of the general specifications include:

- Support for the storage and transfer of internal database registers to/from the ControlLogix processor's controller tags
- Two ports to emulate a Johnson Controls N2 slave
- Supports the following N2 objects:
  - Binary Input: Up to 960 points
  - Analog Input: Up to 300 points
  - Binary Output: Up to 960 points
  - Analog Output: Up to 300 points
- Supported Commands/Sub-commands
  - 0/4: Poll Message No Acknowledge
  - 0/5: Poll Message with Acknowledge
  - 0/9: Status Update
  - 1/1: Read Analog Input Attributes
  - 1/2: Read Binary Input Attributes
  - 1/3: Read Analog Output Attributes
  - 1/4: Read Binary Output Attributes
  - 2/1: Write Analog Input Attributes
  - 2/2: Write Binary Input Attributes
  - 2/3: Write Analog Output Attributes
  - 2/4: Write Binary Output Attributes
  - 7/2/3: Override Analog Output
  - 7/2/4: Override Binary Output
  - F: Identify Device Type
- The following commands are recognized, and acknowledged, but are not communicated in any way to the ControlLogix, and do not return any data:
  - 0/0: Time Update
  - 0/8: Warm Start
  - All other commands return a Bad Command Error Code

- Configurable through the configuration file for the following:
  - Slave Address (assignable individually for Port 1 and 2)
  - Analog Input Object Count
  - Binary Input Object Count
  - Analog Output Object Count
  - Binary Output Object Count

- Warning and Alarming functions performed on Analog Input and Binary Input data types
- Change of State Response buffering
- Communication status error codes and statistics returned per port
- Communication parameter: Baud rate 9600 bps.

Memory mapping is pre-assigned to optimize data access and to ease implementation

A port configured as a Johnson Controls N2 slave permits a remote master to interact with data contained in the module. This data is derived from the ControlLogix processor.

## Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. Compatible products in the inRAX product line also include:

Johnson Controls Metasys Module for SLC (MVI46-N2)

Johnson Controls Metasys Module for CompactLogix (MVI69-N2)

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

## Ordering Information

To order this product, please use the following:

**MVI56-N2** Johnson Controls Metasys Slave Interface Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

### Distributors:

Place your order by email or fax to:

### North American / Latin American / Asia Pacific

orders@prosoft-technology.com,  
fax to +1 661.716.5101

### Europe

europe@prosoft-technology.com,  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.  
January 31, 2007